

Hw4

Grady

2020/11/2

- 1a.

```
paste('apple', 'banana')
```

```
## [1] "apple banana"
```

```
paste0('apple', 'banana')
```

```
## [1] "applebanana"
```

```
x <- c('a', 'b', 'c')
```

```
paste(x, collapse = ', ')
```

```
## [1] "a, b, c"
```

- 1b.

```
presidents <- c("Clinton", "Bush", "Reagan", "Carter", "Ford")
```

```
first.letters <- substr(presidents, 1, 1)
```

```
first.letters
```

```
## [1] "C" "B" "R" "C" "F"
```

- 1c.

```
first.letters.scrambled <- sample(first.letters)
```

```
substr(presidents, 1, 1) = first.letters.scrambled
```

```
presidents
```

```
## [1] "Flinton" "Bush" "Ceagan" "Rarter" "Cord"
```

- 1d.

```
phrase <- "Give me a break"
```

```
phrase <- gsub("Give", "Provide", phrase)
```

```
phrase <- gsub("break", "kit", phrase)
```

```
phrase
```

```
## [1] "Provide me a kit"
```

- 2a.

```
trump.words <- scan('trump.txt',what = 'c')
trump.words.new <- tolower(trump.words)
trump.words.new <- gsub(pattern='[:punct:]',replacement = '',trump.words.new)
```

- 2b.

```
trump.words.new <- trump.words.new[-which(nchar(trump.words.new)==0)]
trump.wordtab.new <-as.data.frame(table(trump.words.new))
```

- 2c.

```
length(trump.words)-length(trump.words.new)
```

```
## [1] 34
```

```
trump.wordtab <-as.data.frame(table(trump.words))
nrow(trump.wordtab)-nrow(trump.wordtab.new)
```

```
## [1] 322
```

- 2d.

```
astrump.wordtab.sorted.new <- trump.wordtab.new[order(trump.wordtab.new$Freq,decreasing = T),]
astrump.wordtab.sorted.new[1:25,]
```

```
##      trump.words.new Freq
## 1121             the  203
##  91              and  150
## 1146             to  130
##  784             of  128
##  809             our   94
## 1244            will   87
##  568             in   79
##  550             i   65
## 1222             we   60
##  512            have   58
##  31              a   54
## 1119            that   52
##  454             for   46
##  598             is   42
##  101             are   39
##  748             my   35
## 1133            this   33
##  789             on   30
## 1123            their  28
##  127             be   27
##  176             by   26
## 1217            was   26
##  84             america 25
## 259            country 25
## 467             from  25
```


- 3a.

```
geo.mean <- function(x,y=1){
  for (i in 1:length(x)) {
    y <- y*x[i]
  }
  a <- length(x)
  return(y^(1/a))
}
geo.mean.two <- function(x,i=1,y=1){
  while(i <= length(x)){
    y <- x[i]*y
    i <- i+1
  }
  a <- length(x)
  return(y^(1/a))
}
```

- 3b.

```
huber <- function(a){
  x <- seq(-2,2,0.01)
  y <- ifelse(abs(x) <= a,x^2,2*a*abs(x)-a^2)
  plot(x,y,type = 'l',main = 'Huber',ylab = "psi(x)")
  text(0,1,'Quadratic')
  b <- a + 0.5
  text(b,1,'Linear')
  text(-b,1,'Linear')
  lines(x=c(a,a),y=c(0,3),lty=2,col='red')
  lines(x=c(-a,-a),y=c(0,3),lty=2,col='red')
}
huber(1)
```

Huber




- 3c.

```
huber <- function(a){
  x <- seq(-2,2,0.01)
  y <- ifelse(abs(x) <= a, x^2, 2*a*abs(x)-a^2)
  plot(x,y,type = 'l',main = 'Huber',ylab = "psi(x)")
  text(0,1,'Quadratic')
  b <- a + 0.5
  text(b,1,'Linear')
  text(-b,1,'Linear')
  mtext('Invented by the great Swiss statistician Peter Huber!',side = 3,outer = T,line = -1)
  lines(x=c(a,a),y=c(0,3),lty=2,col='red')
  lines(x=c(-a,-a),y=c(0,3),lty=2,col='red')
}
huber(1)
```

Invented by the great Swiss statistician Peter Huber!

Huber



- 3d.

```
library(imager)
```

```
## Warning: package 'imager' was built under R version 4.0.3
```

```
## Loading required package: magrittr
```

```
##
```

```
## Attaching package: 'imager'
```

```
## The following object is masked from 'package:magrittr':
```

```
##
```

```
##   add
```

```
## The following objects are masked from 'package:stats':
```

```
##
```

```
##   convolve, spectrum
```

```
## The following object is masked from 'package:graphics':
```

```
##
```


```
##   frame
```

```
## The following object is masked from 'package:base':  
##  
## save.image
```


```
huber = function(x_range = 2, a = 1) {  
  h = function(x) {  
    y = c()  
    for (x_ in x) {  
      if (abs(x_) <= a) {  
        y = append(y, x_ ^ 2) } else {  
          y = append(y, 2 * a * abs(x_) - a ^ 2) } }  
    return (y)  
  }  
  print("Invented by the great Swiss statistician Peter Huber!")  
  peter.huber.jpg = load.image("Peter_huber.jpg")  
  plot(peter.huber.jpg, main = "Peter Huber")  
  curve(h, from = -x_range, to = x_range, ylab = "psi(x)", xlab = "x", main = "Huber")  
  abline(v = -a, col = "red", lty = 2)  
  abline(v = a, col = "red", lty = 1)  
  text(x = -a - 0.5, y = 1, labels = "Linear")  
  text(x = 0, y = 1, labels = "QUadratic")  
  text(x = a + 0.5, y = 1, labels = "Linear") }  
huber()
```

```
## [1] "Invented by the great Swiss statistician Peter Huber!"
```

Peter Huber



Huber



- 4a.

```
load('pros.Rda')
pros.dat.svi <- pros.dat[pros.dat$svi!=0, ]
pros.dat.svi.sd <- vector(length=ncol(pros.dat))
i = 1
while(i<=length(pros.dat.svi.sd)){
  pros.dat.svi.sd[i] <- sd(pros.dat.svi[,i])
  i <- i+1
}
pros.dat.svi.sd
```

```
## [1] 0.6707867 0.3275689 7.8715885 1.3545258 0.0000000 1.0452899 0.6015852
## [8] 25.7344498 0.9251229
```

- 4b.

```
pros.dat.no.svi <- pros.dat[pros.dat$svi==0, ]
pros.dat.no.svi.sd <- vector(length=ncol(pros.dat))
i = 1
while(i<=length(pros.dat.no.svi.sd)){
  pros.dat.no.svi.sd[i] <- sd(pros.dat.no.svi[,i])
  i <- i+1
}
pros.dat.no.svi.sd
```

```
## [1] 1.0685730 0.4479291 7.3105907 1.4782007 0.0000000 1.0379398 0.7088414
## [8] 25.0667600 0.9646403
```

- 4c.

```
for(i in 1:ncol(pros.dat)){
  pros.dat.no.svi.sd[i] <- sd(pros.dat.no.svi[,i])
  pros.dat.svi.sd[i] <- sd(pros.dat.svi[,i])
}
##pros.dat.svi.sd
pros.dat.svi.sd
```

```
## [1] 0.6707867 0.3275689 7.8715885 1.3545258 0.0000000 1.0452899 0.6015852
## [8] 25.7344498 0.9251229
```

```
##pros.dat.no.svi.sd
pros.dat.no.svi.sd
```

```
## [1] 1.0685730 0.4479291 7.3105907 1.4782007 0.0000000 1.0379398 0.7088414
## [8] 25.0667600 0.9646403
```

- 4d.

```
##pros.dat.svi.sd
sapply(pros.dat.svi, function(x) sd(x))
```

```
##      lcavol      lweight      age      lbph      svi      lcp      gleason
## 0.6707867 0.3275689 7.8715885 1.3545258 0.0000000 1.0452899 0.6015852
##      pgg45      lpsa
## 25.7344498 0.9251229
```

```
##pros.dat.no.svi.sd
sapply(pros.dat.no.svi, function(x) sd(x))
```

```
##      lcavol      lweight      age      lbph      svi      lcp      gleason
## 1.0685730 0.4479291 7.3105907 1.4782007 0.0000000 1.0379398 0.7088414
##      pgg45      lpsa
## 25.0667600 0.9646403
```

- 5a.

```
pros.dat.t.stat = mapply(function(x, y) {
  return ((mean(x) - mean(y)) / sqrt(var(x) / length(x) + var(y) / length(y)))
}, pros.dat.svi, pros.dat.no.svi)
pros.dat.t.stat
```

```
##      lcavol      lweight      age      lbph      svi      lcp      gleason
## 8.0351008 1.8265652 1.1069463 -0.8828113      Inf 8.8354810 3.6193860
##      pgg45      lpsa
## 4.9417916 6.8578171
```

- 5b.

```

pros.dat.df = mapply(function(x, y) {
v1 = (var(x) / length(x) + var(y) / length(y)) ^ 2
v2 = (var(x) / length(x)) ^ 2 / (length(x) - 1)
v3 = (var(y) / length(y)) ^ 2 / (length(y) - 1)
return (v1 / (v2 + v3))
}, pros.dat.svi, pros.dat.no.svi)
pros.dat.df

```

```

##      lcavol  lweight      age      lbph      svi      lcp  gleason   pgg45
## 51.17241 42.94873 30.21179 34.33734      NaN 31.75374 36.84259 31.28770
##      lpsa
## 33.02725

```

- 5c.

```

pros.dat.p.val = pt(q=abs(pros.dat.t.stat), df=pros.dat.df, lower.tail = FALSE)
pros.dat.p.val

```

```

##      lcavol      lweight      age      lbph      svi      lcp
## 6.255198e-11 3.736044e-02 1.385266e-01 1.917386e-01      NaN 2.289876e-10
##      gleason      pgg45      lpsa
## 4.408147e-04 1.241127e-05 3.939533e-08

```

```

print(names(pros.dat.p.val[!is.nan(pros.dat.p.val)&pros.dat.p.val < 0.05]))

```

```

## [1] "lcavol" "lweight" "lcp" "gleason" "pgg45" "lpsa"

```

```

print(names(pros.dat.p.val[!is.nan(pros.dat.p.val)&(pros.dat.p.val == min(pros.dat.p.val, na.rm = TRUE))

```

```

## [1] "lcavol"

```

- 5d.

```

my.t.test = function(x, y) {
statistics = (mean(x) - mean(y)) / sqrt(var(x) / length(x) + var(y) / length(y))
v1 = (var(x) / length(x) + var(y) / length(y)) ^ 2
v2 = (var(x) / length(x)) ^ 2 / (length(x) - 1)
v3 = (var(y) / length(y)) ^ 2 / (length(y) - 1)
df = v1 / (v2 + v3)
p.value = pt(q=abs(statistics), df = df, lower.tail = FALSE)
tt = c(statistics, df, p.value)
names(tt) = c("statistics", "df", "p.value")
return (tt)
}
result = mapply(FUN = my.t.test, pros.dat.svi, pros.dat.no.svi)
result

```

```



##      lcavol      lweight      age      lbph svi      lcp
## statistics 8.035101e+00 1.82656523 1.1069463 -0.8828113 Inf 8.835481e+00

```

```
## df          5.117241e+01 42.94872991 30.2117862 34.3373409 NaN 3.175374e+01
## p.value     6.255198e-11 0.03736044 0.1385266 0.1917386 NaN 2.289876e-10
##           gleason      pgg45          lpsa
## statistics 3.619386e+00 4.941792e+00 6.857817e+00
## df          3.684259e+01 3.128770e+01 3.302725e+01
## p.value     4.408147e-04 1.241127e-05 3.939533e-08
```

- 5e.

```
my.t.test = function(x, y) {
  layout(matrix(c(1,1,2,2), 2,2, byrow = TRUE))
  boxplot(x, main = "BoxPlot of x")
  boxplot(y, main = "BoxPlot of y")
  statistics = (mean(x) - mean(y)) / sqrt(var(x) / length(x) + var(y) / length(y))
  v1 = (var(x) / length(x) + var(y) / length(y)) ^ 2
  v2 = (var(x) / length(x)) ^ 2 / (length(x) - 1)
  v3 = (var(y) / length(y)) ^ 2 / (length(y) - 1)
  df = v1 / (v2 + v3)
  p.value = pt(q=abs(statistics), df = df, lower.tail = FALSE)
  tt = c(statistics, df, p.value)
  names(tt) = c("statistics", "df", "p.value")
  return (tt)
}
result = my.t.test(pros.dat.svi$lcavol, pros.dat.no.svi$lcavol)
```



```
result
```

```
## statistics      df      p.value  
## 8.035101e+00 5.117241e+01 6.255198e-11
```